



AAK™ 491/591/691 ACTIVE ANGULAR KIT WITH 90°-DRIVE

SYSTEM SOLUTION WITH 90°-DRIVE
FOR FLEXIBLE SURFACE TREATMENT

The AAK 491/591/691 product family is a finely tuned system package based on the Active Compliant Technology (ACT) and an 90-degree-drive optimized for robot use. This integrated complete solution automates the industrial surface treatment process with individual control of all process parameters: rotation speed, contact force and feed rate. The end-effector is available in 3 different power versions, with a fully integrated servo motor providing the powerful drive. The system is universally compatible with all common abrasive attachments - so no special or manufacturer-dependent consumables are required. The AAK 491/591/691 product family is ideal for many types of surface treatment and offers the highest process quality from one source. The system design is compact and lightweight. The enormously robust end-effector is designed for industrial use, requires little maintenance and delivers performance 24/7.

Surface treatment: Grinding, polishing, satin finishing, radial brushing, cleaning, deburring, cutting
All materials: Steel, aluminum, titanium, magnesium, carbon, plastic, wood, ceramic, coconut fiber...

PATENTED
TECHNOLOGY

FR
FERROBOTICS
perfect feeling

AAK™ 491/591/691

ACTIVE ANGULAR KIT

DEFINED CONTACT FORCE

Interactive compensation of surface tolerances up to 35.5 mm with guaranteed constant real contact force. No adjustment of robot paths.

INTEGRATED GRAVITY COMPENSATION

The defined process force remains constant even with changing orientations. No additional programming effort in the application required.

PASSIVE SAFETY AND HIGH-SPEED CONTROL

Mechatronic actuator and sensor element with high process reliability due to robust mechanical design with integrated passive safety and high-speed control.

FLEXIBLE AUTOMATION

The versatile and user-friendly end-effector can be equipped with a wide range of tools and is suitable for surface finishing of almost all shapes and materials. The system is universally compatible with all common abrasive attachments.



AAK 491/591/691

- even contact force
- automated tolerance compensation
- minimal programming effort and almost no start-up time
- automates almost all manual surface treatment tasks




Control of the feed rate by the robot

Control of the contact force on surfaces by ACT

Angle grinder with doubled output and 90-degree-drive

Control of the rotation speed

SPECIFICATIONS

Ordercode	AAK/491	AAK/591	AAK/691
Max. force (push/pull) [N]	100	160	250
Stroke [mm]	35.5	35.5	48
Dimensions [mm]	Max. 220 x 194 x 259 Bolt circle ISO 9409-1-80-6-M8 Standard flange ø 80	Max. 240 x 210 x 280 Bolt circle ISO 9409-1-80-6-M8 Standard flange ø 80	Max. 343 x 299 x 354 Bolt circle ISO 9409-1-80-6-M8 Standard flange ø 80
Dead weight [kg]	~ 7	~ 9	~ 20
Power supply	<ul style="list-style-type: none"> • 24 V DC • 380 - 500 V AC • ø 8 mm air supply, max. 7 bar, 30 µm, ISO 8573-1 Kl.3 (oil- & water free) 		
Max. speed [rpm]	10,000	10,000	8,500
Rated motor power (S1) [W]	597	1,000	3,000
Motor peak power (S2) [W]	785	2,000	5,900
Surface Treatment	ER16 clamping system and common threaded output drive <ul style="list-style-type: none"> • Grinding • Deburring • Cutting • Polishing • Satin finishing • Radial brushing 		
Air consumption [l/min]	5 - 10		
Ambient temperature during operation [°C]	+5 ... +45		
Protection class	IP65 / if equipped with adequate filters		

FerRobotics Compliant Robot Technology GmbH

Altenbergerstraße 69
Science Park 4 / 5th Floor
4040 Linz, AUSTRIA
office@ferrobotics.at

FerRobotics Inc.

59 Prairie Parkway | 230 W. Baseline Road, Suite 108
60136 GILBERTS | 85282 Tempe
Illinois, USA | Arizona, USA

office@ferrobotics.com



THIS INDUSTRY-PROVEN TOOL IS MULTIFUNCTIONAL AND SUITABLE FOR A WIDE RANGE OF APPLICATIONS.

Dr. Ronald Naderer, CEO

